



AromaTech International  
 605-788 Hamilton Str.  
 Vancouver, BC, V6B 0E9  
 Canada

<b>Ecoscent</b>	<b>R1</b>
Dimensions	300Wx125Hx150Dmm
Weight	3.6kg
Power Supply	220-240V 50Hz, 120V 60Hz
Power Consumption	240V 50W, 120V 66W
Coverage	500 to 1000 m3
Coverage AHU (HVAC)	1000 m3
Scent point connection	1
Adjustable Fragrance Strength	Yes
Arologic Functionality	Optional
Material/Finish	Anodised Aluminium
Color	■

<b>Ecoscent</b>	<b>R2</b>
Dimensions	300Wx125Hx150Dmm
Weight	4.5kg
Power Supply	220-240V 50Hz, 120V 60Hz
Power Consumption	240V 73W, 120V 88W
Coverage	1000 to 2000 m3
Coverage AHU (HVAC)	2000 m3
Scent point connection	2
Adjustable Fragrance Strength	Yes
Arologic Functionality	Optional
Material/Finish	Anodised Aluminium
Color	■

<b>Ecoscent</b>	<b>R4</b>
Dimensions	320Wx220Hx240Dmm
Weight	7.35kg
Power Supply	220-240V 50Hz, 120V 60Hz
Power Consumption	240V 90W, 120V 85W
Coverage	2000 to 4000 m3
Coverage AHU (HVAC)	4000 m3
Scent point connection	4
Adjustable Fragrance Strength	Yes
Arologic Functionality	Optional
Material/Finish	Anodised Aluminium
Color	■

<b>Ecoscent</b>	<b>R6</b>
Dimensions	320Wx220Hx240Dmm
Weight	7.35kg
Power Supply	220-240V 50Hz, 120V 60Hz
Power Consumption	240V 90W, 120V 85W
Coverage	4000 to 6000 m3
Coverage AHU (HVAC)	6000 m3
Scent point connection	6
Adjustable Fragrance Strength	Yes
Arologic Functionality	Optional
Material/Finish	Anodised Aluminium
Color	■

<b>Ecoscent</b>	<b>R</b>
Dimensions	100Wx320Hx106Dmm
Weight	1.95kg
Coverage	500 to 1000 m3
Coverage AHU (HVAC)	1000 m3
Silencer	Standard
Hose-coupling	Optional
Fragrance Cartridge	1 x 450ml
Material/Finish	Anodised Aluminium
Color	■

All features and technical data subject to change without notice.  
 Copyright © AromaTech International. All rights reserved.